

since 1964..

YAKAN AYDINLATMA®


Manufacturing and Trade of Outdoor Decorative Lighting Products
Best Globe®

2026

YKN Green Power Solar Lighting

R&D

- Professional solar lighting products, developed over 10 years of research and development.
- Successful sales performance sustained for 7 years.
- Production and sales tailored to institutions, based on the solar lighting manufacturing activities listed in our industrial registration certificate.
- 60% domestic production



Contact



+90 212 243 30 08
+90 535 015 90 10



www.yakanaydinlatma.com
info@yakanaydinlatma.com.tr



Factory & Showroom
İkitelli OSB Tormak San. Sit. C
blok, NO 2 Başakşehir İstanbul
Türkiye



IK08 IP66	Average Lighting Area 80m ²	Average Lighting Duration 14 Hours	2 YEAR WARRANTY
MAX Lm 2400			

Y.A.126030 - 90 W

- **Product Model:** 90 W (equivalent energy) professional solar lighting
- **Recommended Installation Height:** Up to 5 meters
- **LED Type:** High-efficiency solar optic lens, Nichia LED 6500K, 2400 Lm
- **Average Lighting Area:** 80 m²
- **Body:** Aluminum
- **Battery Capacity:** 4 units of 6 Ampere battery group, LifeP04 (minimum lifespan of 5 years)
- **Solar Panel:** 14.25 W Monocrystalline
- **Product Function:** Motion sensor, high light - low light level performance mode
- 16 hours of lighting duration achieved with 6-8 hours of sunlight exposure.
- **Dimensions:** 300*100 mm armature, **Panel:** 420*300 mm including fittings
- **Weight:** 3 kg
- **Amortization Period (Approximate):** 2.5 years



IK08 IP66	Average Lighting Area 80m ²	Average Lighting Duration 14 Hours	2 YEAR WARRANTY
MAX Lm 2400			

Y.A.127020 - 70 W

- **Product Model:** 70 W (equivalent energy) professional solar lighting
- **Recommended Installation Height:** Up to 4 meters
- **LED Type:** High-efficiency solar optic lens, Nichia LED 6500K, 2200 Lm
- **Average Lighting Area:** 80 m²
- **Body:** Aluminum. **Connection parts:** Steel with galvanized coating and electrostatic paint
- **Battery Capacity:** 2 units of a 6 Ampere battery group, LifeP04 (minimum lifespan of 5 years)
- **Solar Panel:** 7 W Monocrystalline
- **Product Function:** Motion sensor, high light - low light level performance mode
- Achieves 14 hours of lighting with 6-8 hours of sunlight exposure
- **Dimensions:** 190*260*40 mm
- **Weight:** 2 kg
- **Amortization Period (Approximate):** 2.5 years.



IK08 IP66	Average Lighting Area 90m ²	Average Lighting Duration 17-20 Hours	2 YEAR WARRANTY
MAX Lm 2400			

Y.A.127025 - 100 W - 150 W

- **Product Model:** 100 W - 150 W (equivalent energy) professional solar lighting
- **Recommended Installation Height:** Up to 5 meters
- **LED Type:** High-efficiency solar optic lens, Nichia LED 6500K, 2400 Lm
- **Average Lighting Area:** 90 m²
- **Body:** aluminum, **Connection Parts:** steel with galvanized coating and electrostatic paint.
- **Battery Capacity:** 4 units of a 6 Ampere battery group, LifeP04 (with a minimum lifespan of 5 years)
- **Solar Panel:** 14.25 W Monocrystalline
- **Product Function:** Motion sensor, high light - low light level performance mode
- Achieves 17-20 hours of lighting with 6-8 hours of sunlight exposure
- **Dimensions:** 360*550*450 mm (including panel and arm length)
- **Weight:** 6.5 kg.
- **Amortization Period (Approximate):** 2.5 years.



Important Warning Regarding All Solar LED Lighting Fixtures: Due to the high weight and wind load of our products, it is the customer's responsibility to ensure the static load-bearing capacity of any mounting surface (walls, roofs, facades, poles, etc.). Our company accepts no liability for detachment, toppling, or damages arising from the inadequacy of the mounting surface or structure.

Y.A.127030 - 100 W - 150 W

- **Product Model:** 100 W - 150 W (equivalent energy) professional solar lighting
- **Recommended Installation Height:** Up to 5 meters
- **LED Type:** High-efficiency solar optic lens, Nichia LED 6500K, 2400 Lm
- **Average Lighting Area:** 90 m²
- **Body:** Steel with galvanized coating and electrostatic paint
- **Battery Capacity:** 4 units of 6 Ampere battery group, LifeP04 (minimum lifespan of 5 years)
- **Solar Panel:** 14.25 W Monocrystalline
- **Product Function:** Motion sensor, high light-low light level performance mode
- 17-20 hours of lighting with 6-8 hours of sunlight exposure
- **Dimensions:** 200*560*220 mm (varies according to armature angle)
- **Weight:** 4.6 kg
- **Amortization Period (Approximate):** 2.5 years



Y.A.127032 - 100 W - 150 W

- **Product Model:** 100 W - 150 W (equivalent energy) professional solar lighting
- **Recommended Installation Height:** Up to 5 meters
- **LED Type:** High-efficiency solar optic lens, Nichia LED 6500K, 2400 Lm
- **Average Lighting Area:** 90 m²
- **Body:** Steel with galvanized coating and electrostatic paint
- **Battery Capacity:** 4 units of 6 Ampere battery group, LifeP04 (minimum lifespan of 5 years)
- **Solar Panel:** 14.25 W Monocrystalline
- **Product Function:** Motion sensor, high light-low light level performance mode
- 17-20 hours of lighting with 6-8 hours of sunlight exposure
- **Dimensions:** 360*480*200 mm (varies according to armature angle)
- **Weight:** 6 kg
- **Amortization Period (Approximate):** 2.5 years



Important Warning Regarding All Solar LED Lighting Fixtures: Due to the high weight and wind load of our products, it is the customer's responsibility to ensure the static load-bearing capacity of any mounting surface (walls, roofs, facades, poles, etc.). Our company accepts no liability for detachment, toppling, or damages arising from the inadequacy of the mounting surface or structure.





Suitable for fitting Ø60mm-Ø76mm poles.

MAX Lm 5200	Average Lighting Area 100m²	Average Lighting Duration 20-22 Hours	
-----------------------	---	---	---

Y.A.127040 - 100 W - 150 W

- **Product Model:** 100 W - 150 W (equivalent energy) professional solar lighting
- **Recommended Installation Height:** 6 meters and above
- **LED Type:** High-efficiency solar optic lens, Nichia LED 6500K 3100 Lm-5200 Lm
- **Average Lighting Area:** 100 m²
- **Body:** Aluminum **Connection Parts:** steel with galvanized coating and electrostatic paint
- **Battery Capacity:** 8 units of 6 Ampere battery group, LifeP04 (**minimum lifespan of 5 years**)
- **Solar Panel:** 60 W Monocrystalline
- **Product Function:** Motion sensor, high light-low light level performance mode
- 20-22 hours of lighting with 6-8 hours of sunlight exposure
- **Dimensions:** 540*620*800 mm (varies according to panel angle)
- **Weight:** 21 kg
- **Amortization Period (Approximate):** 2.5 years



Suitable for fitting Ø60mm-Ø76mm poles.

MAX Lm 5200	Average Lighting Area 100m²	Average Lighting Duration 20-22 Hours	
-----------------------	---	---	---

Y.A.127060 - 100 W - 150 W

- **Product Model:** 100 W - 150 W (equivalent energy) professional solar lighting
- **Recommended Installation Height:** 6 meters and above
- **LED Type:** High-efficiency solar special lens, Nichia LED 6500K, 3100 Lm - 5200 Lm
- **Average Lighting Area:** 100 m²
- **Body:** Steel with galvanized coating and electrostatic paint
- **Battery Capacity:** 8 units of 6 Ampere battery group, LifeP04 (**minimum lifespan of 5 years**)
- **Solar Panel:** 25 W Monocrystalline
- **Product Function:** Motion sensor, high light-low light level performance mode
- 20-22 hours of lighting with 6-8 hours of sunlight exposure
- **Dimensions:** 360*480*200 mm (varies according to armature angle)
- **Weight:** 6.5 kg
- **Amortization Period (Approximate):** 2.5 years



Suitable for fitting Ø60mm-Ø76mm poles.

MAX Lm 6700	Average Lighting Area 150-200m²	Average Lighting Duration 20-22 Hours	
-----------------------	---	---	---

Y.A.127075 - 150 W - 200 W

- **Product Model:** 150 W - 200 W (equivalent energy) professional solar lighting
- **Recommended Installation Height:** Between 6-10 meters
- **LED Type:** High-efficiency solar special lens, Nichia LED 6500K 3900 Lm-6700 Lm
- **Average Lighting Area:** 150-200 m²
- **Body:** Aluminum, **Connection Parts:** steel with galvanized coating and electrostatic paint
- **Battery Capacity:** 8 units of 6 Ampere battery group, LifeP04 (**minimum lifespan of 5 years**)
- **Solar Panel:** 75 W Monocrystalline
- **Product Function:** Motion sensor, high light-low light level performance mode
- 20-22 hours of lighting with 6-8 hours of sunlight exposure
- **Dimensions:** 540*620*800 mm (varies according to panel angle)
- **Weight:** 22 kg
- **Amortization Period (Approximate):** 2.5 years



Suitable for fitting Ø60mm-Ø76mm poles.

MAX Lm 6700	Average Lighting Area 160-200m²	Average Lighting Duration 20-22 Hours	
-----------------------	---	---	---

Y.A.127080 - 250 W - 300 W

- **Product Model:** 250 W - 300 W (equivalent energy) professional solar lighting
- **Recommended Installation Height:** Between 10-12 meters
- **LED Type:** High-efficiency solar optic lens, Nichia LED 6500K 3900 Lm - 6700 Lm
- **Average Lighting Area:** 160-200 m²
- **Body:** Aluminum, **Connection Parts:** Steel with Galvanized Coating + Electrostatic Paint
- **Battery Capacity:** 8 units of 6 Ampere battery group, LifeP04 (**minimum lifespan of 5 years**)
- **Solar Panel:** 110 W Monocrystalline
- **Product Function:** Motion sensor, high light-low light level performance mode
- 20-22 hours of lighting with 6-8 hours of sunlight exposure
- **Dimensions:** 540*620*800 mm (varies according to panel angle)
- **Weight:** 23 kg
- **Amortization Period (Approximate):** 2.5 years



Important Warning Regarding All Solar LED Lighting Fixtures: Due to the high weight and wind load of our products, it is the customer's responsibility to ensure the static load-bearing capacity of any mounting surface (walls, roofs, facades, poles, etc.). Our company accepts no liability for detachment, toppling, or damages arising from the inadequacy of the mounting surface or structure.

The prices do not include TAX and shipping. Please inquire about your discount rates.

Y.A.127500 - 150 W - 200 W



Suitable for fitting Ø76mm poles.

MAX Lm 6700	Average Lighting Area 150-200m²	Average Lighting Duration 20-22 Hours	
-----------------------	---	---	---

- **Product Model:** 150 W - 200 W (equivalent energy) professional solar lighting
- **Recommended Installation Height:** Between 6-10 meters
- **LED Type:** High-efficiency solar optic lens, Nichia LED 6500K, 3740 Lm - 6700 Lm
- **Average Lighting Area:** 150-200 m²
- **Body:** Steel with Galvanized Coating + Electrostatic Paint
- **Battery Capacity:** 8 units of 6 Ampere battery group, LifeP04 (minimum lifespan of 5 years)
- **Solar Panel:** 75 W Monocrystalline
- **Product Function:** Motion sensor, high light-low light level performance mode
- 20-22 hours of lighting with 6-8 hours of sunlight exposure
- **Dimensions:** 540*620*250 mm (varies according to armature angle)
- **Weight:** 15 kg
- **Amortization Period (Approximate):** 2.5 years

Y.A.127095 - 150 W - 200 W



Suitable for fitting Ø76mm - Ø89mm poles.

MAX Lm 6700	Average Lighting Area 150-200m²	Average Lighting Duration 20-22 Hours	
-----------------------	---	---	---

- **Product Model:** 150 W - 200 W (equivalent energy) professional solar lighting
- **Recommended Installation Height:** Between 6-10 meters
- **LED Type:** High-efficiency solar optic lens, Nichia LED 6500K, 3740 Lm - 6700 Lm
- **Average Lighting Area:** 150-200 m²
- **Body:** Steel with Galvanized Coating + Electrostatic Paint
- **Battery Capacity:** 8 units of 6 Ampere battery group, LifeP04 (minimum lifespan of 5 years)
- **Solar Panel:** 75 W Monocrystalline
- **Product Function:** Motion sensor, high light-low light level performance mode
- 20-22 hours of lighting with 6-8 hours of sunlight exposure
- **Dimensions:** 540*620*250 mm (varies according to armature angle)
- **Weight:** 15 kg
- **Amortization Period (Approximate):** 2.5 years

Y.A.128004 - 350 W - 400 W



Suitable for fitting Ø60mm-Ø76mm poles.

MAX Lm 6750	Average Lighting Area 250-300m²	Average Lighting Duration 12-14 Hours	
-----------------------	---	---	---

- **Product Model:** 350 W - 400 W (equivalent energy) professional solar lighting
- **Recommended Installation Height:** Between 8-10 meters
- **LED Type:** High-efficiency solar optic lens, Nichia LED 6500K, 4200-6750 Lm
- **Average Lighting Area:** 250-300 m²
- **Body:** Metal
- **Battery Capacity:** 16 units of 6 Ampere battery group, LifeP04 (minimum lifespan of 5 years)
- **Solar Panel:** 110 W Monocrystalline
- **Product Function:** Full-performance lighting with high light mode
- 12-14 hours of full-performance lighting with 6-8 hours of sunlight exposure
- **Dimensions:** 790mm width*1175mm length*790mm height mm (varies depending on the panel angle)
- **Weight:** 25 kg
- **Amortization Period (Approximate):** 2.5 years,

Y.A.128018 - 420 W - 450 W



Suitable for fitting Ø60mm-Ø76mm poles.

MAX Lm 6750	Average Lighting Area 270-350m²	Average Lighting Duration 12-14 Hours	
-----------------------	---	---	---

- **Product Model:** 420 W - 450 W (equivalent energy) professional solar lighting
- **Recommended Installation Height:** 12 meters
- **LED Type:** High-efficiency solar optic lens, Nichia LED 6500K, 4250-6750 Lm
- **Average Lighting Area:** 270-350 m²
- **Body:** Metal
- **Battery Capacity:** 24 units of 6 Ampere battery group, LifeP04 (minimum lifespan of 5 years)
- **Solar Panel:** 110 W Monocrystalline
- **Product Function:** High light mode for full-performance lighting
- 12-14 hours of full-performance lighting with 6-8 hours of sunlight exposure
- **Dimensions:** 790mm width * 1175mm length * 790mm height mm (varies depending on the panel angle)
- **Weight:** 26 kg
- **Amortization Period (Approximate):** 2.5 years

The prices do not include TAX and shipping. Please inquire about your discount rates.



MAX Lm 6700	Average Lighting Area 150-200m ²	Average Lighting Duration 20-22 Hours
----------------	--	--



Y.A.130070 - 250w-300w

- **Product Model:** 250w-300w (equivalent energy) professional solar armature (without pole)
- **Recommended Installation Height:** Max 7 meters
- **LED Type:** High-efficiency solar optic lens, Nichia LED 6500K, 3740 Lm - 6700 Lm
- **Average Lighting Area:** 150-200 m²
- **Body:** Steel with Galvanized Coating + Electrostatic Paint
- **Battery Capacity:** 12 units of 6 Ampere battery group, LifeP04 (minimum lifespan of 5 years)
- **Solar Panel:** 86 W Monocrystalline
- **Product Function:** Motion sensor, high light-low light level performance mode
- 20-22 hours of lighting with 6-8 hours of sunlight exposure
- **Dimensions:** 70x70cm
- **Weight:** 23,5
- **Amortization Period (Approximate):** 2.5 years



Important Warning Regarding All Solar LED Lighting Fixtures: Due to the high weight and wind load of our products, it is the customer's responsibility to ensure the static load-bearing capacity of any mounting surface (walls, roofs, facades, poles, etc.). Our company accepts no liability for detachment, toppling, or damages arising from the inadequacy of the mounting surface or structure.

12V Professional Solar Lighting Pole

2026

Material:

- Steel
- Galvanized Coating
- Electrostatic Paint
- Reinforced Flange



2026 Solar Lighting Poles (Galvanized Coating)

Y.A.145002	2 M
Y.A.145003	3 M
Y.A.145004	4 M
Y.A.145005	5 M
Y.A.145006	6 M
Y.A.145007	7 M

Important Warning Regarding All Solar LED Lighting Fixtures: Due to the high weight and wind load of our products, it is the customer's responsibility to ensure the static load-bearing capacity of any mounting surface (walls, roofs, facades, poles, etc.). Our company accepts no liability for detachment, toppling, or damages arising from the inadequacy of the mounting surface or structure.

**YAKAN
AYDINLATMA®**



TS EN40-5



Factory/Showroom Address

İkitelli OSB Tormak Sanayi Sitesi C Blok No 2 İstanbul Başakşehir
Türkiye

Contact Number
+90 212 243 30 08





- Material: Steel, with Galvanized Coating + Electrostatic Paint
- 2026 Solar Lighting Roof and Wall Mounting Arm



Important Warning Regarding All Solar LED Lighting Fixtures: Due to the high weight and wind load of our products, it is the customer's responsibility to ensure the static load-bearing capacity of any mounting surface (walls, roofs, facades, poles, etc.). Our company accepts no liability for detachment, toppling, or damages arising from the inadequacy of the mounting surface or structure.

YAKAN
AYDINLATMA®



TS EN40-5



Factory/Showroom Adress

İkitelli OSB Tormak Sanayi Sitesi C Blok No 2 İstanbul Başakşehir
Türkiye


Contact Number
+90 212 243 30 08



since 1964..

YAKAN AYDINLATMA®

Manufacturing and Trade of Outdoor Decorative Lighting Products
Best Globe



You can visit our website to explore our other
decorative products, which include over 2,000 varieties



1964'den bugüne..

YAKAN AYDINLATMA®

Dış Mekan Dekoratif Aydınlatma Mamülleri İmalat ve Ticaret
Best Globe

İkitelli O.S.B. Tormak Sanayi Sitesi C Blok No 2 Başakşehir İstanbul Türkiye
Showroom Phone (pbx) : +90 212 243 30 08
Factory Phone (pbx) : +90 212 485 13 43
Factory Mobile Whatsapp : +90 535 015 90 10
www.yakanaydinlatma.com / info@yakanaydinlatma.com.tr